

# TRAMIGO

TRACKING & CONNECTIVITY



COMPLETE SOLUTION

## TRAMIGO FCT PLUS

MAINTAIN SECURITY AND RAISE EFFICIENCY

The Tramigo FCT Plus is ideal for Malaysian car rental businesses. This all-in-one eSIM tracking SIRIM approved solution features embedded connectivity and software access, allowing you to easily track your fleet from anywhere, anytime. Simple plug-and-play installation and compatibility with a wide range of vehicles, from electric cars to heavy-duty trucks (9-90V) you can improve and secure fleet management utilizing driving, maintenance and odometer alerts.



## TRAMIGO FCT PLUS FEATURES



IMMOBILIZE IN  
CASE OF MISUSE



REAL-TIME  
TRACKING



GEO-FENCE  
FEATURES



AFFORDABLE  
TRACKING  
SOLUTION



SECURITY  
ALARMS



DRIVING  
ALERTS



BUILT-IN  
BATTERY



PLUG & PLAY  
WITH CRAB CLAW



BUILT-IN  
eSIM

# TRAMIGO SOFTWARE

Tramigo offers software solutions which allows you to monitor your vehicles at your control center or from your mobile devices:

## • TRAMIGO CLOUD

TramigoCloud allows you to track your fleet behind a secure web login and puts a full control center within your reach wherever you go. With centralised updates the latest features are always immediately available to all of our security focused customers. TramigoCloud is recommended for fleet management.



## • TRAMIGO APP

TramigoApp is an easy but secure way to track and monitor your vehicles anytime and anywhere. TramigoApp allows you to monitor and track your vehicles, staff, or family directly on your phone. Additional features includes trip reports, usage history reporting, geofence and setting alarms. Available for free on App Store and Google Play.



## TRAMIGO FCT PLUS TECHNICAL DATA

Dimension	85(L) x 45(W) x 17(H) mm
Network	LTE/GSM/GPRS
Frequency(4G+2G)	LTE-FDD B1/B2/B3/B4/B5/B7/B8/B28/B66 GSM :850/900/1800/1900Mhz
Location accuracy	<5 meters CEP
Time To Fix (open sky)	Cold start <35s Hot start <1s
Working voltage	9-90VDC
GPRS Protocol	Class12, TCP/IP
Operating temp.	-20°C to +70°C
Back up battery	200mAh /3.7V Li-Polymer battery
Standby & Working consumption GSM/GPS Antenna	5mA~50mA
Memory storage	2000 data
Micro USB interface	Flash firmware/Configuration
Power interface	8 PIN or 4PIN version
Firmware and configuration OTA	Supported